





Single semi-floating 270mm Braking® petal disc with dual-piston caliper

Single 250mm Braking® petal disc with

100/90-19

n	n	M		n
r	U	W	ľΕ	K

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression

Ratio

14.1:1

Fuel System DFI® with 44mm Keihin throttle body and

dual injectors

Ignition Digital CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Frame Type

Ground

Clearance

Rear Tire

Front Brakes

Rear Brakes

Aluminum perimeter

single-piston caliper

Rake/Trail 28.0°/4.6 in

Overall Length 85.8 in

Overall Width 32.3 in

Overall Height 49.8 in

Seat Height 37.4 in

Curb Weight 226.4 lb without fuel / 236.5 lb*

13.2 in

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

Color Choices Lime Green

Warranty Not Available

PERFORMANCE

Front
Suspension /
Wheel Travel

48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping/12.4 in

Rear Suspension / Wheel Travel New Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in

Front Tire

80/100-21



