BRUTE FORCE® 300









POWER

Engine 4-stroke, 1-cylinder, SOHC

Displacement 271cc

Bore x Stroke 72.7 x 65.2mm

Compression Ratio 11.0:1

15.9 lb-ft @ 6500 rpm **Maximum Torque**

Fuel System Keihin CVK32 carburetor

Ignition DC-CDI

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive 2WD, Shaft

Fuel Capacity 3.2 gal

Electronic Power No Steering (EPS)

Turning Radius 9.2 ft

Towing Capacity 500 lb

Total Rack Capacity

110 lb

Rack Capacity,

Front/Rear

44/66 lb

Lighting

(2) 35W headlights, 5W taillight and 21W stoplight

CAPABILITY

Front Suspension /	Independent double wishbone/5.2 in
Wheel Travel	

Rear Suspension / Wheel Travel

Swingarm/5.6 in

Front Tires AT 22 x 7-10 Maxxis tubeless

Rear Tires AT 22 x 10-10 Maxxis tubeless

Front Brakes Dual 180mm discs

Rear Brakes Single 180mm disc

Ground Clearance 6.1 in

Starting System Electric

DETAILS

Frame Type	Double cradle, steel

Track Front/Rear 33.5/32.7 in

Overall Length 75.4 in

Overall Width 42.5 in

Overall Height 46.1 in

Seat Height 33.3 in

Curb Weight 535.8 lb*

Wheelbase 45.9 in

Instruments Speedometer, odometer, clock, fuel gauge and

coolant temp light

Color Choices Super Black, Bright White

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit ecuador.kawasaki-la.com for full product details.