## KX<sup>™</sup>250









## **POWER**

**Engine** 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

**Bore x Stroke** 78.0 x 52.2mm

Compression

Ratio

14.1:1

DFI® with 44mm Keihin throttle body and **Fuel System** 

dual injectors

Ignition Digital CDI

**Transmission** 5-speed, return shift, with wet multi-disc

manual clutch

**Final Drive** Chain **Rear Brakes** 

**Front Brakes** 

**Rear Tire** 

Single semi-floating 270mm Braking®

petal disc with dual-piston caliper

Single 250mm Braking® petal disc with

single-piston caliper

110/90-19

## **PERFORMANCE**

**Front** Suspension / **Wheel Travel** 

48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping/12.4 in

Rear Suspension / **Wheel Travel**  New Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in

**Front Tire** 80/100-21 **DETAILS** 

**Frame Type** 

Aluminum perimeter

28.0°/4.6 in Rake/Trail

86.2 in **Overall Length** 

**Overall Width** 32.3 in

**Overall Height** 50.0 in

Ground 13.6 in Clearance

**Seat Height** 37.8 in

**Curb Weight** 227.6 lb without fuel / 237.7 lb\*

**Fuel Capacity** 1.64 gal

Wheelbase 58.5 in

**Color Choices** Lime Green

Not Available Warranty

Scan with camera to view videos. key features and more.

