KX[™]250X







P	N	W	/F	R
	u	W		•

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression 1

Ratio

14.1:1

Fuel System DFI® with 44mm Keihin throttle body and

dual injectors

Ignition Digital CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

PERFORMANCE

Front
Suspension /
Wheel Travel

48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping /12.4 in

Rear Suspension / Wheel Travel Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and

adjustable preload/12.4 in

Front Tire 80/100-21

Rear Tire 110/100-18

Front Brakes Single semi-floating 270mm Braking®

petal disc with dual-piston caliper

Rear Brakes Single 240mm Braking® petal disc with

single-piston caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 27.8/4.8 in

Overall Length 85.4 in

Overall Width 32.3 in

Overall Height 49.6 in

Ground 13.0 in Clearance

Seat Height 37.2 in

Curb Weight 230.1 lb without fuel/240.2 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.3 in

Color Choices Lime Green

Warranty Not Available



