## NINJA® ZX™-6R KRT EDITION







P	N	١	N	F	R
	u			_	

4-stroke, In-Line Four, DOHC, 16-valve, liquid-**Engine** 

cooled

12.9:1

**Displacement** 636cc

**Bore x Stroke** 67.0 x 45.1mm

Compression

**Ratio** 

DFI® with 38mm Keihin throttle bodies (4) and oval **Fuel System** 

sub-throttles

TCBI with Electronic Advance Ignition

**Transmission** 6-speed, return shift

**Final Drive** Sealed chain

**Electronic Rider** 

Aids

Kawasaki Traction Control (KTRC), Power Modes (Full/Low), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Kawasaki Quick Shifter

(KQS) (upshift only)

## PERFORMANCE

**Front Suspension** / Wheel Travel

41mm inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs /4.7 in

Rear Suspension / **Wheel Travel** 

Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully

adjustable spring preload/5.9 in

**Front Tire** 

120/70 ZR17

**Rear Tire** 180/55 ZR17

**Front Brakes** Dual semi-floating 310mm discs with dual radial-

mounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

(ABS only)

Single 220mm petal discs with single-piston **Rear Brakes** 

caliper, Kawasaki Intelligent anti-lock Brake

System (KIBS) (ABS only)

## **DETAILS**

**Frame Type** Aluminum perimeter

Rake/Trail 23.5° / 4.0 in

**Overall Length** 79.7 in

**Overall Width** 28.0 in

**Overall Height** 43.3 in

**Ground Clearance** 5.1 in

**Seat Height** 32.7 in

**Curb Weight** 436.6 lb\* (ABS), 432.2 lb\* (non-ABS) 50-State Model,

434.4 lb\* (ABS), 430.0 lb\* (non-ABS) 49-State Model

**Fuel Capacity** 4.5 gal

Wheelbase 55.1 in

**Special Features** 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

**Color Choices** Lime Green/Ebony

Warranty 12 Month Limited Warranty

Scan with camera to view videos. key features and more.

