## 2025 **KLX®300**







## Deer Tire 1 C .. 10 **POWER** Engine 4-stroke single, DOHC, liquid-cooled Displacement 292cc **Bore x Stroke** 78.0 x 61.2mm **DETAILS** Compression 11.1:1 Ratio DFI® with 34mm Keihin throttle body **Fuel System** Ignition CDI 6-speed, return shift with wet multi-dis Transmission manual clutch **Final Drive** Chain

## PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable compression damping /10.0 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/9.1 in
Front Tire	3.00 x 21

Rear Tire	4.6 X 18
Front Brakes	Single 250mm petal disc with a dual-piston caliper
Rear Brakes	Single 240mm petal disc with single-piston caliper

	Frame Type	Tubular, Semi Double Cradle
sc	Rake/Trail	26.7°/4.2 in
	Overall Length	85.6 in
	Overall Width	32.3 in
	Overall Height	46.7 in
	Ground Clearance	10.8 in
) in	Seat Height	35.2 in
	Curb Weight	302.1 lb*
	Fuel Capacity	2.0 gal
oring	Wheelbase	56.7 in
	Color Choices	Lime Green, Battle Gray, Cypher Camo Gray (Matte)
	Warranty	12 Month Limited Warranty





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit ecuador.kawasaki-la.com for full product details.