MULE PRO-MX™ LE







POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft, Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

35.7 amp

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.6 in

Rear Suspension / **Wheel Travel**

Double wishbone/9.1 in

Front Tires Rear Tires

25 x 8-12, radial 25 x 10-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, mechanical disc

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

699 lb / 600 lb CA Model

33.4 x 44.1 x 9.1 in

Cargo Bed Load

Capacity

Payload Capacity 1,200 lb

Seating Capacity

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights, (2) LED headlights

DETAILS

Overall Width

Overall Length 110.0 in

Overall Height 75.8 in

Curb Weight 1,594.2 lb* / 1,596.4 lb* CA Model

60.0 in

Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator,

EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

Additional Features Roof, Cast Aluminum Wheels

Color Choices Deep Blue

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.