
# NINJA® ZX™-6R KRT EDITION









### **POWER**

**Engine** 4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled

Displacement 636cc

**Bore x Stroke** 67.0 x 45.1mm

**Compression Ratio** 12.9:1

Maximum 127.0 hp1 @ 13,000 rpm Horsepower

DFI® with 38mm Keihin throttle bodies (4) and oval **Fuel System** 

sub-throttles

TCBI with Electronic Advance Ignition

**Transmission** 6-speed, return shift

**Final Drive** Sealed chain

(Full/Low), Kawasaki Intelligent anti-lock Brake

(KQS) (upshift only)

### **Electronic Rider** Aids

Kawasaki Traction Control (KTRC), Power Modes System (KIBS) (ABS only), Kawasaki Quick Shifter

### **PERFORMANCE**

Front Suspension / **Wheel Travel** 

41mm inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs/4.7 in

**Rear Suspension / Wheel Travel** 

Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully adjustable spring

preload/5.9 in

120/70 ZR17 **Front Tire** 

**Rear Tire** 180/55 ZR17

**Front Brakes** Dual semi-floating 310mm discs with dual radial-

> mounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

(ABS only)

Single 220mm petal discs with single-piston caliper, Rear Brakes

Kawasaki Intelligent anti-lock Brake System (KIBS)

(ABS only)

## **DETAILS**

**Frame Type** Aluminum perimeter

Rake/Trail 23.5° / 4.0 in

**Overall Length** 79.7 in

**Overall Width** 28.0 in

**Overall Height** 43.3 in

**Ground Clearance** 5.1 in

**Seat Height** 32.7 in

436.6 lb\* (ABS), 432.2 lb\* (non-ABS) 50-State Model, **Curb Weight** 

**Fuel Capacity** 4.5 gal

Wheelbase 55.1 in

**Special Features** 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

434.4 lb\* (ABS), 430.0 lb\* (non-ABS) 49-State Model

**Color Choices** Lime Green/Ebony/Pearl Blizzard White

12 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit ecuador.kawasaki-la.com for full product details.