
## VERSYS® 650 ABS









## **POWER**

4-stroke, 2-cylinder, DOHC, liquid-cooled, 4 **Engine** valves per cylinder parallel twin

**Displacement** 649cc

**Bore x Stroke** 83.0 x 60.0mm

10.8:1

Compression

Ratio

Maximum **Torque** 

44.8 lb-ft

**Fuel System** 

DFI® with 38mm Keihin throttle bodies (2)

Ignition

TCBI with electronic advance

**Transmission** 

6-speed with positive neutral finder

**Final Drive** 

Sealed chain

## **PERFORMANCE**

Front Suspension / **Wheel Travel** 

41mm hydraulic telescopic fork with stepless adjustable rebound and preload/5.9 in

Rear Suspension /

**Wheel Travel** 

Single offset laydown shock with remote adjustable spring preload/5.7 in

**Front Tire** 

120/70 ZR-17

**Rear Tire** 160/60 ZR-17

**Front Brakes** Dual 300mm petal-style discs with 2-piston

calipers, ABS

**Rear Brakes** Single 250mm petal-style disc with single-

piston caliper, ABS

## **DETAILS**

**Frame Type** Double pipe diamond frame constructed from high-tensile steel

25°/4.3 in Rake/Trail

**Overall Length** 85.2 in

**Overall Width** 33.1 in

**Overall Height** 53.5 in/55.9 in (windshield down/up)

Ground 6.7 in Clearance

**Seat Height** 33.3 in

**Curb Weight** 482.9 lb\*

**Fuel Capacity** 5.5 gal

Wheelbase 55.7 in

**Color Choices** Pearl Robotic White/Metallic Spark Black

Warranty 12 month limited warranty



