NEW 2026 NINJA® ZX™-10R









POWER

Horsepower

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio

Maximum 190.0 hp¹ @ 11,500 rpm

13.0:1

Maximum Torque 82.7 lb-ft @ 11,300 rpm

Fuel System DFI® with 47mm throttle bodies

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider Aids

Economical Riding Indicator, Electronic Cruise Control,
Kawasaki Launch Control Mode (KLCM), Sport-Kawasaki
TRaction Control (S-KTRC), Kawasaki Intelligent anti-lock

Brake System (KIBS) (ABS only), Anti-lock Brake System (ABS) (ABS only), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS), IMU-Enhanced

Chassis Orientation Awareness

DETAILS

Front Tire

Rear Tire

Front Brakes

Rear Brakes

Frame Type Twin spar, cast aluminum

Rake/Trail 25.0°/4.1 in

120/70 ZR17

190/55 ZR17

(and ABS)

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height 46.5 in

Ground Clearance 5.1 in

Seat Height 32.5 in

Estimated Dry Weight 425.5 lb** (ABS), 421.1 lb** (non-ABS) 49-State Model

Curb Weight 463.0 lb* (ABS), 458.6 lb* (non-ABS) 49-State Model

Fuel Capacity 4.5 gal
Wheelbase 57.1 in

37.1111

Special Features 5" All-digital TFT color instrumentation, All-LED lighting,

Öhlins steering damper, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via

Dual 330mm semi-floating Brembo discs with radial-mount 4-piston Brembo M50 monobloc calipers (and ABS)

Single 220mm disc with aluminum single-piston caliper

RIDEOLOGY THE APP MOTORCYCLE***

Color Choices Lime Green/Blue 24, Metallic Matte Graphenesteel Gray/

Metallic Spark Black/Pearl Storm Gray

Warranty 12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Showa Balance Free Fork (BFF) with external compression chamber, rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel Horizontal back-link with Showa Balance Free Rear Cushion (BFRC) lite gas-charged shock with piggyback reservoir, rebound and compression damping, spring preload adjustability/4.2 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit ecuador.kawasaki-la.com for full product details.