

NUEVA 2026

NINJA® ZX™-10R



- LIME GREEN/BLUE 24
- METALLIC MATTE GRAPHENESTEEL GRAY/  
METALLIC SPARK BLACK/PEARL STORM GRAY

POTENCIA		Neumático delantero	
Motor	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Neumático trasero	120/70 ZR17
Cilindrada	998cc	Frenos delanteros	190/55 ZR17
Diámetro por carrera	76.0 x 55.0mm	Frenos traseros	Dual 330mm semi-floating Brembo discs with radial-mount 4-piston Brembo M50 monobloc calipers (and ABS)
Relación de compresión	13.0:1		Single 220mm disc with aluminum single-piston caliper (and ABS)
Potencia máxima	190.0 hp¹ @ 11,500 rpm	DETALLES	
Par motor máximo	82.7 lb-ft @ 11,300 rpm	Tipo de chasis	Twin spar, cast aluminum
Sistema de combustible	DFI® with 47mm throttle bodies	Ángulo de dirección/Avance	25.0° / 4.1 in
Encendido	TCBI with Electronic Advance	Largo total	82.1 in
Transmisión	6-speed, return shift	Ancho total	29.5 in
Transmisión final	Sealed chain	Altura del asiento	46.5 in
Asistencia electrónica para el piloto	Economical Riding Indicator, Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Sport-Kawasaki Traction Control (S-KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Anti-lock Brake System (ABS) (ABS only), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness	Distancia al suelo	5.1 in
RENDIMIENTO		Altura del asiento	32.5 in
Suspensión delantera/recorrido del neumático	43mm inverted Showa Balance Free Fork (BFF) with external compression chamber, rebound and compression damping, spring preload adjustability/4.7 in	Peso seco estimado	425.5 lb** (ABS), 421.1 lb** (non-ABS) 49-State Model
Suspensión trasera/recorrido del neumático	Horizontal back-link with Showa Balance Free Rear Cushion (BFRC) lite gas-charged shock with piggyback reservoir, rebound and compression damping, spring preload adjustability/4.2 in	Peso en orden de marcha	463.0 lb* (ABS), 458.6 lb* (non-ABS) 49-State Model
		Depósito de combustible	4.5 gal
		Distancia entre ejes	57.1 in
		Características especiales	5" All-digital TFT color instrumentation, All-LED lighting, Öhlins steering damper, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDELOGY THE APP MOTORCYCLE***
		Colores disponibles	Lime Green/Blue 24, Metallic Matte Graphenesteel Gray/Metallic Spark Black/Pearl Storm Gray
		Garantía	12 Month Limited Warranty

Escanear con cámara para ver videos, características clave y más.

¹Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

²Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*\*RIDELOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visite [ecuador.kawasaki-la.com](http://ecuador.kawasaki-la.com) para obtener detalles completos del producto.